

# Preassembled indoor units



## General information

|                   |                          |
|-------------------|--------------------------|
| Model             | R586HPWY002              |
| Construction type | All-electric indoor unit |
| Weight (bruto)    | 9,2 kg                   |
| Weight            | 7,8 kg                   |
| Dimensions        | 390 x 350 x 165 mm       |

## Components

|                             |                           |
|-----------------------------|---------------------------|
| Capacity inline heater      | 3kW                       |
| Voltage 16A                 | 230V                      |
| Dry run protection          | 70 °C                     |
| Housing                     | EPP                       |
| Number of circulation pumps | 2                         |
| Maximum delivery head       | 8m                        |
| Flow control                | Intelligent PWM           |
| Flow speed                  | 0.5 – 2 m <sup>3</sup> /h |
| Flow direction              | Check valve               |
| Maximum operating pressure  | 3 Bar                     |
| Air separator               | Automatic                 |

## Connection diameters

|                 |      |
|-----------------|------|
| Heat pump       | 1 ½" |
| Central heating | 1 ½" |
| Tap water (DHW) | 1 ½" |



## General information

|                   |                     |
|-------------------|---------------------|
| Model             | WHP                 |
| Construction type | Hybride indoor unit |
| Weight (bruto)    | 7,5 kg              |
| Weight            | 6,1 kg              |
| Dimensions        | 390 x 350 x 165 mm  |

## Components

|                             |                           |
|-----------------------------|---------------------------|
| Voltage 16A                 | 230V                      |
| Housing                     | EPP                       |
| Number of circulation pumps | 1                         |
| Maximum delivery head       | 8m                        |
| Flow control                | Intelligent PWM           |
| Flow speed                  | 0.5 – 2 m <sup>3</sup> /h |
| Flow direction              | Check valve               |
| Maximum operating pressure  | 3 Bar                     |
| Air separator               | Automatic                 |

## Connection diameters

|                 |                     |
|-----------------|---------------------|
| Heat pump       | 1 ½"                |
| Central heating | 1 ½"                |
| Check valve     | 6/4"F - 6/4"M / 1"F |