

GIACOMINI S.p.A. Tel. (+39) 0322 923111 Fax (+39) 0322 96256

Fax (+39) 0322 9625 info@giacomini.com www.giacomini.com Sede legale ed amministrativa: Via per Atzo. 39 - 28017 San Maurizio d'Opaglio (NO) ITALIA R.E.A. della CCIAA di Novara n. 194845 PLIVA 0179229031 - Codice Fiscale 01856080062 Identificativo IVA IT 01792290031 Capitale Sociale: € 50.66.520 l.v.

Società soggetta a direzione e coordinamento della Alberto Giacomini Holding S a s, di Alberto Giacomini



SUPPLIER DECLARATION (Dich1 05 49 00 EN)

(according to UNI CEI EN ISO/IEC 17050-1:2010)

The Manufacturer **GIACOMINI S.p.A.** located in Italy, San Maurizio d'Opaglio (NO) - Via per Alzo, no. 39, under its own responsibility **ATTESTS** that:

the ball valves with red lever, of the ranges R850 (product codes R850X021, R850X022, R850X023, R850X024, R850X025, R850X026), DR850, R851 (product codes R851X021, R851X022, R851X023, R851X024, R851X025, R851X026), R854 (product codes R854X023, R854X024, R854X024, R854X025, R854X026), R854LX026) and R859 in dimensions from ¼" up to 1 ¼" included, destined to be used in the following applications and according to the following use limits:

- Fluids: water, glycol solutions (max 50%), non-dangerous gases and liquid hydrocarbons;
- Minimum working temperature: -20°C glycol solutions (max 50%);
- Maximum working temperature with dry saturated steam: 185°C with 1,05 MPa (10.5 bar);
- Maximum working pressure at 20°C with water and non-dangerous gases: 3,5 MPa (35 bar) ¼" thru ¾"

2,8 MPa (28 bar) 1" and 1 1/4";

- Temperature range with liquid hydrocarbons: -20÷60°C;
- Maximum working pressure at 20°C with liquid hydrocarbons: 1,2 MPa (12 bar)

are properly designed and manufactured using materials suitable to the distribution of water, non-dangerous gases and liquid hydrocarbons according to the sound engineering practice in use, which ensures the safety of use in compliance with the technical requirements and the specific prescriptions, pertinent and applicable, referred to art.4, par. 3, of PED 2014/68/UE Directive with particular reference to Tab.7 of Annex II – Conformity assessment tables.

The subject valves are also manufactured respecting design and production processes in compliance with requirements of **UNI EN ISO 9001:2015** standard.

Moreover, GIACOMINI S.p.A. company ATTESTS

that the ball valves here identified, in application of the above-mentioned technical requirements and prescriptions, are also accompanied by sufficient use instructions and are not "CE marked" since they have characteristics lower than the limits given at paragraph 1, letters a), b) and c) and at paragraph 2 of 2014/68/UE PED Directive.

Signed for and on behalf of Giacomini S.p.A.

Marco Rosa Beyson

The Technical Manager

Ing. Marco Rosa Brusin

San Maurizio D'Opaglio, 20.06.2023