

# R752

## Ball valve for water for heating systems, full port



Energy  
Management

Datasheet  
0645EN  11/2022



Ball valve, with female-female threaded connections with nut and gasket, with adjustable tail piece (valve length adjustment: 8 mm), specific for meters connection. Full port.

### Versions and product codes

PRODUCT CODE	CONNECTIONS	FINISHING	HANDLE TYPE	HANDLE COLOR	NOTES
R752X003	G 1/2"F x Nut G 3/4"F	Chrome plated brass	T-handle	Red	Nut with 3 holes of 2,5 mm, to seal the meter



**GIACOMINI**  
WATER E-MOTION



Giacomini S.p.A.  
Via per Alzo 39, 28017 San Maurizio d'Opaglio (NO) Italia  
[consulenza.prodotti@giacomini.com](mailto:consulenza.prodotti@giacomini.com)  
[+39 0322 923372](tel:+390322923372) - [giacomini.com](http://giacomini.com)

## Technical data

### Main features and materials


- Suitable for water for heating/cooling systems
- Full port
- Valve made of UNI EN 12165 CW617N chrome plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Aluminium T-handle, red painted
- Adjustable tail piece with valve length adjustment of 8 mm

### Field of applications

- Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions)
- Max. working pressure at 20 °C with water: 4,2 MPa (42 bar)

## Dimensions and Kv

PRODUCT CODE	DN	A [mm]	A' [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	H' [mm]	Kv
R752X003	15	74	82	30	56	18	63	wr.26	wr.30	12,7



## Product specifications

### R752

Ball valve, with female-female threaded connections with nut and gasket, with adjustable tail piece (valve length adjustment: 8 mm), specific for meters connection. Suitable for water for heating/cooling systems. Valve made of UNI EN 12165 CW617N chrome plated brass. Full port. Aluminium T-handle, red painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions). Max. working pressure at 20 °C with water: 4,2 MPa (42 bar).

**⚠ Safety Warning.** Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

**♻ Package Disposal.** Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

**ℹ Additional information.** For more information, go to [giacomini.com](http://giacomini.com) or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

**♻ Product Disposal.** Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.