


## Thermoformed insulation panel made of EPS, for radiant floor systems

Datasheet  
0985EN 10/2023



Thermoformed insulation panel R979B for radiant floor systems. Consisting of expanded polystyrene foam (EPS150) with black thermoformed polystyrene protection layer.

### ► Versions and product codes

PRODUCT CODE	SIZE [mm] T=pitch - h=height	N. OF SHEETS	TOTAL USEFUL SURFACE [m <sup>2</sup> ]	TYPE OF PACKAGING
R979BY103	T50 - h32	22	24,64	Packed in plastic sack
R979BY104	T50 - h42	16	17,92	
R979BY184	T50 - h48	14	15,68	
R979BY105	T50 - h52	12	13,44	
R979BY106	T50 - h62	10	11,20	
R979BY186	T50 - h65	9	10,08	
R979BY187	T50 - h73	8	8,96	
R979BY107	T50 - h75	8	8,96	
R979BY188	T50 - h90	6	6,72	Packed in an open box
R979BY113	T50 - h32	22	24,64	
R979BY114	T50 - h42	16	17,92	
R979BY194	T50 - h48	14	15,68	
R979BY115	T50 - h52	12	13,44	
R979BY116	T50 - h62	10	11,20	
R979BY196	T50 - h65	9	10,08	
R979BY197	T50 - h73	8	8,96	
R979BY117	T50 - h75	8	8,96	
R979BY198	T50 - h90	6	6,72	

## Technical data

### Stocking conditions

- The panels must not be exposed to direct sunlight
- Stocking must be carried out in a dry and protected area, at temperatures above 5 °C and below 50 °C
- Keep the panels away from chemical agents
- Keep the panels away from open flames and heat sources

**▲ WARNING.** Do not expose to direct sunlight, even after installation, up to screed casting.

### R979BY103, R979BY113

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	32 mm sheet: 10 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	0,29 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

### R979BY104, R979BY114

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	42 mm sheet: 20 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	0,59 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

**R979BY184, R979BY194**

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	48 mm sheet: 26 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	0,76 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

**R979BY105, R979BY115**

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	52 mm sheet: 30 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	0,88 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

**R979BY106, R979BY116**

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	62 mm sheet: 40 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	1,18 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

**R979BY186, R979BY196**

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	65 mm sheet: 43 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	1,26 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

**R979BY187, R979BY197**

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	73 mm sheet: 51 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	1,50 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black


**R979BY107, R979BY117**

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	75 mm sheet: 53 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	1,56 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

## R979BY188, R979BY198

INSULATION PANEL	
Useful dimensions	1400 x 800 mm
Useful surface	1,12 m <sup>2</sup>
Panel dimensions	1450 x 850 mm
Panel surface	1,23 m <sup>2</sup>
Total thickness	90 mm sheet: 68 mm + protrusion: 22 mm
Pipe diameter	16÷17 mm
Allowed pitches	Multiples of 50 mm
INSULATION SHEET	
Material	Expanded polystyrene EPS150
Thermal conductivity, $\lambda_D$	0,034 W/(m K)
Thermal resistance, $R_\lambda$	2,00 m <sup>2</sup> K/W
Min. resistance to 10% crushing	150 kPa
Reaction to fire	Class E
Classification according to EN13163	EPS-EN13163-L(3)-W(3)-T(2)-CS(10)150-WL(T)0,5-Z30-70
PROTECTION LAYER	
Material	Thermo-formed polystyrene
Thickness	0,5 mm
Film color	Black

## ➔ Main features



The special configuration of the thermoformed protrusion enables to firmly grip pipes with a 16-17 mm external diameter.

Thermoformed insulation panels R979B save time when laying the pipes and can be used to create circuits with multiples of 50 mm.

The available thicknesses, with total heights ranging between 32 mm and 90 mm, enable to install radiant floor heating and cooling systems in any type of work site, even with limited space, such as renovation projects.

All panels R979B feature a very simple and efficient connection system.


The surface coating is 50 mm larger than the insulation sheet underneath on both sides.

The two larger edges overlapping the contiguous panels connect to each other, creating a homogeneous support base for the radiant circuits with no heat bridges, which are typical of panels lacking a solid connection system.

## ► Laying



Laying of thermoformed insulation panels R979B is quick and easy thanks to the larger edges on both sides that provide state-of-the-art connections.



After fitting edge strip K369A on the walls (the insulation that prevents heat bridges and allows minimum dilations of the floor), lay and connect the panels making sure the subsequent rows follow an offset pattern.

Offset rows prevent panels from raising when the support surface is disconnected or for stiff pipes, especially in bends, that tend to raise for the mechanical memory acquired when rolled up.

The two protruding edges are removed with a cutter from sheet 1 which is positioned in the corner most suitable to start laying. Sheet 2 is trimmed only on its longer side. The shorter edge will be used to couple sheet 1.

This step must be repeated on every sheet of the first row.


The subsequent rows will be laid by fitting each panel to the next row with the same offset.

When laying is completed, and before casting the screed, we recommend installing electro-welded sheet K393 with large meshes over the panel.

The dimensions required for a residential radiant panel system are represented by the height of the thermoformed insulation panel (32-90 mm) added to the screed thickness (at least 30 mm, according to UNI EN 1264-4) and the thickness of the tile or glued pit surface finish.

**⚠ WARNING.** Do not lay the product when room temperature is below 5 °C.

## ➤ Components and dimensions



PRODUCT CODE	PANEL "A" TOTAL HEIGHT [mm]	INSULATION/PROTRUSION HEIGHT [mm]	SCREED "B" MINIMUM HEIGHT [mm]	"A+B" MINIMUM HEIGHT COATING "C" EXCLUDED [mm]
R979BY103, R979BY113	32	10/22	30	62
R979BY104, R979BY114	42	20/22	30	72
R979BY184, R979BY194	48	26/22	30	78
R979BY105, R979BY115	52	30/22	30	82
R979BY106, R979BY116	62	40/22	30	92
R979BY186, R979BY196	65	43/22	30	95
R979BY187, R979BY196	73	51/22	30	103
R979BY107, R979BY117	75	53/22	30	105
R979BY188, R979BY198	90	68/22	30	125

## ➤ Reference standards

- EN 1264: Floor heating – Systems and components.
- EN 13163: Thermal insulation products for buildings – Factory made products of expanded polystyrene (EPS).



## Product specifications

### **R979BY103, R979BY113**

Thermoformed insulation panel for radiant floor systems. Color black. Height 32 mm (insulation sheet 10 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 0,29 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY104, R979BY114**

Thermoformed insulation panel for radiant floor systems. Color black. Height 42 mm (insulation sheet 20 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 0,59 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY184, R979BY194**

Thermoformed insulation panel for radiant floor systems. Color black. Height 48 mm (insulation sheet 26 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 0,76 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY105, R979BY115**

Thermoformed insulation panel for radiant floor systems. Color black. Height 52 mm (insulation sheet 30 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 0,88 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY106, R979BY116**

Thermoformed insulation panel for radiant floor systems. Color black. Height 62 mm (insulation sheet 40 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 1,18 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY186, R979BY196**

Thermoformed insulation panel for radiant floor systems. Color black. Height 65 mm (insulation sheet 43 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 1,26 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY187, R979BY197**


Thermoformed insulation panel for radiant floor systems. Color black. Height 73 mm (insulation sheet 51 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 1,50 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.


### **R979BY107, R979BY117**


Thermoformed insulation panel for radiant floor systems. Color black. Height 75 mm (insulation sheet 53 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 1,56 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

### **R979BY188, R979BY198**

Thermoformed insulation panel for radiant floor systems. Color black. Height 90 mm (insulation sheet 68 mm, protrusion 22 mm). Consisting of expanded polystyrene insulation sheet (EPS150) and 0,5 mm polystyrene protection layer. For Ø 16÷17 mm pipes. Laying center distance: multiples of 50 mm. Dimensions: 1450x850 mm (useful dimensions: 1400X800 mm). Panel useful surface 1,12 m<sup>2</sup>. Thermal conductivity 0,034 W/(m K). Thermal resistance ( $R = s/\lambda$ ) 2,00 m<sup>2</sup>K/W. Min. resistance to 10 % crushing, 150 kPa. Resistance to fire: class E.

 **Safety Warning.** Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

 **Package Disposal.** Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

 **Additional information.** For more information, go to [giacomini.com](http://giacomini.com) or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

 **Product Disposal.** Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.